



Innovator in Flow Measurement Technology



ISO9001
certified

Founded in 1983, Transonic Systems Inc. is a progressive manufacturer of biomedical flow measurement equipment. Incubated at Cornell University, the company sells its ultrasound transit-time flowmeters, laser Doppler perfusion monitors and flow/dilution hemodialysis monitor to researchers, surgeons, nephrologists and equipment manufacturers around the world. With more than 70 employees, its R & D, manufacturing, and sales and marketing activities are based at its headquarters on Dutch Mill Road in Ithaca NY.

MISSION

We strive to deliver to our customers, on time, error-free products and services that exceed their expectations for value.

CUSTOMER SERVICE

Customer Service is integral to Transonic Systems. We seek to place expert technology into your hands. As the ears and voice of Transonic Systems, we listen to and learn from you. With your input, Transonic Systems engineers and physicists design, develop, and manufacture quality flow measurement products that meet your needs for repeatability and accuracy. We succeed by serving you.

RESEARCH APPLICATIONS

Support

Ongoing applications support is provided through our newsletter, *Transit Times*, and through an extensive bibliography of application notes, surgical protocols, technical notes, videos and published references.

We appreciate your enthusiasm and willingness to help us document your experiences and share techniques that will assist the newcomer to our technology.

Development

Transonic Systems also promotes development of new applications. Specialty projects and OEM co-engineering proposals receive the high priority that our customers have come to expect. Please call us if you do not find the answer to your query in this catalog.

Transonic Flow-QC Products — Clinical product lines for quality patient care are available, but are not featured in this catalog.

The **Surgical Flowmeter**: intraoperative flow measurements *during* surgery.

Bypass Flowmeter and sterile tubing flowsensors: actual delivered blood flow *within* intensive care extracorporeal circuits.

Hemodialysis Monitor: blood line flow, recirculation, vascular access flow *during* the hemodialysis treatment.

Laser Doppler Perfusion Alarm Monitor: for postoperative monitoring of tissue flap viability.

Please contact Transonic Systems or your distributor for more information about these products.

Transonic



Quality Care

To Order: Call 607-257-5300 or 800-353-3569; Fax 607-257-7256

Table of Contents



Ordering Information

Prices are subject to change without notice and are listed in US dollars (*shipping and handling additional*) F.O.B. Factory, Ithaca, NY.

Proforma quotations, including shipping, available upon request.
Contact: Margo Sosa

Research Products Manager

or Douglas Collins,

Laser Doppler Applications Manager

Tel: 800-353-3569;

Fax: 607-257-7256,

E-Mail: margo@tran.mhs.comuserve.com

doug@tran.mhs.comuserve.com

Terms of sale: NET 30 days. Rental and lease programs are available. VISA / MasterCard accepted for purchases, rentals and repairs. All orders require a signed purchase order (*fax, OK*).

International

Transonic Systems sells its products worldwide through a network of distributors (*see back cover*). For more information, please contact Catherine Roberts, Mgr., International Distributor Network Via fax (*# above*) or E-Mail: cathy@tran.mhs.comuserve.com

www.transonic.com

Transonic Systems' dynamic new web site is now on line and receiving monthly updates. For the latest information check our web site, www.transonic.com

Repairs / Returns

Before returning a product for repair, call Transonic customer service for a RMA (*return material authorization*) number. Follow return directions in the operator's manual. For warranty repairs or returns, please return the item in the original packaging. Non-warranty repairs require a purchase order before repair.

Volume Flow Measurement Systems

Ultrasonic Transit-Time Technology

Acute/Chronic Animal Studies

T106/T206 Gold Standard Research Flowmeter

Measurement Capabilities/Specs	.3
Electives	.6
Perivascular Flowprobes	.7
Probes for the Rodent Model	.8
Microcirculation Probes	.9
Cardiac Output Probes, 8 - 36 mm	.10
Probes, 0.5 - 24 mm (<i>pictures to scale 1 - 24 mm</i>)	.13
Probe Specifications	.16
Accessories	.18
Reflector Styles	.19
Connectors	.20
Extension Cables	.22
We Still Support	.23
To Order	.24
Applications Support	
Probe Size Recommendations	.26
Research Support Bibliography	.29

Extracorporeal/Mock Circulatory Models

T109R Lab Tubing Flowmeter	.31
Measurement Capabilities/Specs	.32
X-Series Sterile Tubing Flowsensors	.35
T106/T206 Research Flowmeter	.37
Sterile Tubing Flowsensors	.38
In-Line Flowprobes	.39
To Order	.41

Appendix: *Ultrasonic Transit-Time Technology, Calibration; Theory, Validation References* .42

Tissue Perfusion Measurements

Laser Doppler Technology

Microcirculation Measurements

BLF21-Series Laser Doppler Monitors	.47
Applications	.48
Laser Doppler Probes	.52
Applications Support	.55
To Order	.56

Data Acquisition, Pressure Recordings

Strip Chart, Computer Interface Option with	
WINDAQ Data Acquisition / WINDAQ Playback	.57
Pressur recording	.61

Glossary	.62
Policies & Procedures	.64