



R-, S- V- Series Probes *cont.*

5 — 12 mm Perivascular Probes, specifications on pages 16,17

S-Series

R-Series

5 mm probe

New!



5RB: 5 mm R-Series, back cable exit only; L reflector with slide, dog renal

6 mm probes



6SS: 6 mm S-Series probe, side cable exit, L reflector with slide



6RS: 6 mm R-Series probe, side cable exit L reflector with slide

Probes pictured are actual sizes.

8 mm probes



8SS: 8 mm S-Series probe, side cable exit, L reflector with slide



8RS: 8 mm R-Series probe, side cable exit, L reflector with slide

Probes can be custom configured for your application with back or side exit cables and reflectors from standard reflector components (*see page 19*).

10 mm probe



10SB: 10 mm S-Series probe, back cable exit, L reflector with slide

12 mm probe



12SS: 12 mm S-Series probe, side cable exit, U reflector

R-, S- V- Series Probes cont.



14 - 24 mm Perivascular Probes, specifications on next page

S-Series

14 mm probe

14SS: 14 mm S-Series probe, side cable exit, U reflector



16 mm probe

16SB: 16 mm S-Series probe, back cable exit, U reflector



20 mm probe

For measurements on the ascending aorta and pulmonary artery, see A-Series probes, pages 10-12

20SS: 20mm S-Series probe, side cable exit, U reflector, shown with silicone shield



24 mm probe

Probes pictured are actual sizes.

24SS: 24 mm S-Series probe, side cable exit, U reflector only for use with T108/T208 & T101D / T201D flowmeters

